

ARCH01 Specification Sheet



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, AND POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. PLEASE NOTE TONING WILL VARY FROM DOOR TO DOOR.

SHELTERED EXTERIOR OPTIONS AVAILABLE.

Door Weights - kg/m²

| | |
|---------------|------|
| Hollow | 10.5 |
| Polystyrene | 10.5 |
| Solid | 28.5 |
| Steel per L/M | 2.0 |

Honeycomb Hollow Core



Particle Board Core



Polystyrene Core



ARCH01 Specialty Veneer Door Details

| | |
|-------------------------------|---|
| Description | Stile is NZ Rimu, main panel is American White Oak (choice of crown or quarter cut) |
| Veneer Position | NZ Rimu stile is 225mm wide, American White Oak makes up the balance of the door |
| Top Rail | 324mm |
| Side Stiles | 110mm |
| Mid Rails | 160mm |
| Glazing Opening Width | Door Width Less 220mm |
| Glazing Opening Height | 90mm |

Core Availability

| | Hollow | Polystyrene | Solid |
|-----------|--------|-------------|-------|
| 1980 High | • | • | • |
| 2400 High | • | • | • |
| 2700 High | • | • | • |
| Oversize | N/A | N/A | N/A |

Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

| | Rails | Stiles | Lockblocks |
|--------------|----------|----------|-------------|
| Hollow | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Polystyrene | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Solid | Ex 35mm | Ex 35mm | N/A |
| 960mm Wide + | Ex 105mm | Ex 105mm | N/A |
| >2400mm High | Ex 105mm | Ex 105mm | N/A |

Skin and Thickness Options

| | 36mm | 39mm | 42mm |
|-------------|-------------|-------------|------------|
| Hollow | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Polystyrene | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Solid | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |

- 'Oversize' is doors over 1210mm wide or 2700mm high
- Staining veneer doors is at your own risk. Hallmark Group accepts no responsibility for the finished quality of a stained veneer door
- All architectural collection doors are made to order

- * All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overheight doors