

## Jarrah Specification Sheet



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. OTHER VENEER OPTIONS ARE AVAILABLE ON REQUEST.

### Door Weights - kg/m<sup>2</sup>

Hollow	10.5
Polystyrene	10.5
Solid	28.5
Steel per L/M	2.0

### Jarrah

<b>Description</b>	Deep dark Brown- Red colour, Strong grain. Wide range of colour variation from pale pink tones through to very dark brown
<b>Veneer Features</b>	Some small black pips and tight knots permissible
<b>Veneer Cuts Available</b>	Crown Cut only
<b>Standard Matching Pattern</b>	Book Matched, Matched pairs are available
<b>Country of Origin</b>	Western Australia
<b>Sustainably Harvested</b>	Yes
<b>Veneer Hardness</b>	Very Hard

### Core Availability

	Hollow	Polystyrene	Solid
1980 High	•	•	•
2400 High	•	•	•
2700 High	•	•	•
Oversize	N/A	•	N/A

### Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

	Rails	Stiles	Lockblocks
<b>Hollow</b>	Ex 35mm	Ex 35mm	400 x 70mm*
<b>Polystyrene</b>	Ex 35mm	Ex 35mm	400 x 70mm*
<b>Solid</b>	Ex 35mm	Ex 35mm	N/A
<b>960mm Wide +</b>	Ex 105mm	Ex 105mm	N/A
<b>&gt;2400mm High</b>	Ex 105mm	Ex 105mm	N/A

### Skin and Thickness Options

	36mm	39mm	42mm
<b>Hollow</b>	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Polystyrene</b>	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Solid</b>	4.75mm Skin	4.75mm Skin	6.0mm Skin
<b>Oversize</b>	6.0mm Skin, option of 38 or 43mm		

- 'Oversize' is doors over 1210mm wide or 2700mm high
- All veneer doors are made to order

- \* All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overheight doors