


## VVPJ Specification Sheet




PLEASE NOTE: GLASS IS NOT INCLUDED. ALL PANELS ARE BEADED WITH REBATED BEADING AS STANDARD. FLUSH BEADING AVAILABLE ON REQUEST.

4.75MM MDF SKIN (FOR INTERIOR USE)



PREMIUM TEMPERED HARDBOARD SKIN (FOR SHELTERED EXTERIOR USE)



FLUSH BEADING



REBATED BEADING



### VVPJ Panel Cut-Out Dimensions (mm)

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Top, Bottom and Mid Rails (Per Rail) | Door Height less 560mm Divided by 9 |
| Side Stiles                          | 110mm*                              |
| Glazing Panel Width                  | Door Width Less 220mm**             |
| Glazing Panel Height                 | 70mm                                |

\* Side Stiles increase to 160mm when doors are ordered with steel stiffeners

\*\* Glazing Panel Width formula with steel stiffeners changes to 'Door Width less 320mm'

|                 | Core Availability |             |       | Available Finishes |                     |
|-----------------|-------------------|-------------|-------|--------------------|---------------------|
|                 | Hollow            | Polystyrene | Solid | Un-Primed          | U.V Primed          |
| 1980 High       | N/A               | N/A         | •     | MTO                | Ex-Stock (38mm S/C) |
| Up to 2400 High | N/A               | N/A         | •     | MTO                | Ex-Stock (38mm S/C) |
| 2700 High       | N/A               | N/A         | •     | MTO                | MTO                 |
| Oversize        | N/A               | N/A         | N/A   | MTO                | N/A                 |

|                     | Stile, Rail and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide |          |            |
|---------------------|---|----------|------------|
|                     | Rails   | Stiles   | Lockblocks |
| Hollow (1980)       | N/A   |          |            |
| Hollow (Up to 2400) | N/A   |          |            |
| Polystyrene         | N/A   |          |            |
| Solid (Up to 2400)  | Ex 140mm  | Ex 35mm  | N/A        |
| 960mm Wide +        | Ex 105mm  | Ex 105mm | N/A        |
| >2400mm High        | Ex 105mm  | Ex 105mm | N/A        |

### Skin and Thickness Options (MDF Skins)

|             | 34.5mm | 37mm | 38mm        | 39.5mm      | 42mm       |
|-------------|--------|------|-------------|-------------|------------|
| Hollow      | N/A    | N/A  | N/A         | N/A         | N/A        |
| Polystyrene | N/A    | N/A  | N/A         | N/A         | N/A        |
| Solid       | N/A    | N/A  | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Oversize    | N/A    | N/A  | N/A         | N/A         | N/A        |

- All doors over 1210 wide supplied un-primed
- 'Oversize' is doors over 1210mm wide or 2700mm high

- Stock doors are standard sizes between 410mm and 910mm wide

- Tempered hardboard faced doors available for sheltered exterior doors, 38mm, 39.5mm or 42mm options