

Radiata Specification Sheet



ALL DOORS ARE AVAILABLE IN HOLLOWCORE, SOLIDCORE, POLYSTYRENE CORE. ALL DOORS ARE AVAILABLE UP TO 2700MM HIGH. OTHER VENEER OPTIONS ARE AVAILABLE ON REQUEST.

Door Weights - kg/m²

| | |
|---------------|------|
| Hollow | 10.5 |
| Polystyrene | 10.5 |
| Solid | 28.5 |
| Steel per L/M | 2.0 |

Radiata

| | |
|----------------------------------|---|
| Description | A yellowy white colour with prominent growth rings |
| Veneer Features | Some small pips permissible, wide range of grain patterns |
| Veneer Cuts Available | Crown cut |
| Standard Matching Pattern | Book Matched. Matched pairs are available |
| Country of Origin | New Zealand |
| Sustainably Harvested | Yes |
| Veneer Hardness | Softwood |

Core Availability

| | Hollow | Polystyrene | Solid |
|-----------|--------|-------------|-------|
| 1980 High | • | • | • |
| 2400 High | • | • | • |
| 2700 High | • | • | • |
| Oversize | N/A | • | N/A |

Door Frame and Lockblock Configuration 1980 up to 2400 High Doors 410-910mm Wide

| | Rails | Stiles | Lockblocks |
|------------------------|----------|----------|-------------|
| Hollow | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Polystyrene | Ex 35mm | Ex 35mm | 400 x 70mm* |
| Solid | Ex 35mm | Ex 35mm | N/A |
| 960mm Wide + | Ex 105mm | Ex 105mm | N/A |
| >2400mm High | Ex 105mm | Ex 105mm | N/A |

Skin and Thickness Options

| | 36mm | 39mm | 42mm |
|--------------------|----------------------------------|-------------|------------|
| Hollow | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Polystyrene | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Solid | 4.75mm Skin | 4.75mm Skin | 6.0mm Skin |
| Oversize | 6.0mm Skin, option of 38 or 43mm | | |

- 'Oversize' is doors over 1210mm wide or 2700mm high
- All veneer doors are made to order

- * All hollow and polystyrene doors have double lock blocks, 400mm long for 1980 doors, and 800mm long for overhead doors